

specifications of building

SHRI KRISHNA TOWERS FOR MS MENTHOL PVT.LTD SITUATED AT- VILAGE MAJHABLI , TEHSIL, CHANDAUSI ,DISTT. SAMBHAL

- 1 EXCAVATION IN FOUNDATION
2.50 mtr. TO N.G.L
FOR RAFT FOOTING
- 2 CEMENT CONC. IN FOUNDATION
1:2:4 MIX IN cum
- 3 FIRST CLASS BRICKS WORK IN FOUNDATION
1:6 CEMENT MORTAR
- 4 R.C.C WORK FOOTING ,COLUMN
WITH SHARE WALL
UPTO TWL. FLOOR AS PER STRUCTURAL DETAILS M30,M25
- 7 FIRST CLASS BRICK WORK IN SUPER STRUCTURE
1:6 CEMENT MORTAR
- 10 M.S.REINFORCEMENT IN R.C.C ROOF SLAB,R.C.C COLMUN
& R.C.C. BEAMS WITH CHARACTERSTIC STRENGTH OF 500 N/sq. mm.
- 11 PLASTER ON WALL BOTH SIDE
12 MM THICK 1:4 CEMENT & SAND
- 12 WOOD WORK
FOR DOORS & WINDOWS IN
SALL & SHISAM ,FLUSH DOORS
- 13 FLOOR TILES WITH STANDARD QUALITY
FLOORING WITH BASE CONC
- 14 WALL TILES WITH STANDARD QUALITY
TOILET & KITCHEN
- 15 TWO COATS OF EXTERIOR COLOUR
BOTH SIDE OF WALL
- 16 FOR ELECTRIFICATION ALL MATERIALS USE BY ARKAYLITE & HAVELLS
- 17 FOR WATER SUPPLY AND SANITATION MATERIALS USE BY APOLLO,CERA,HINDWARE

