

<u>LEGEND</u>:

M VALVE

NON RETURN VALVE

DIFFUSER

) PRESSURE GAUGE

SEWAGE TREATMENT PLANT DETAILS **RCC TANKS DETAILS:** S.NO. DESCRIPTION CAPACITY **EQUALIZATION TANK - 1 CHAMBER** 110 KL Each FAB TANK - 4 CHAMBER 2. 25 KL Each 3. TUBE SETTLER - 2 CHAMBER 8 M2 Each FILTER FEED TANK - 1 CHAMBER 45 KL Each 4. 5. SLUDGE HOLDING TANK - 1 CHAMBER 70 KL Each 6. TREATED WATER STORAGE TANK - 1 CHAMBER 130 KL Each

SEWAGE TREATMENT PLANT CAPACITY = 440 KLD (TO BE INSTALLED IN TWO MODULES OF 220 KLD EACH)

project GARDENIA GLORY
AT SECTOR - 46, NOIDA

title SCHEMATIC FLOW DIAGRAM
SEWAGE TREATMENT PLANT (1020 KLD)

drg. no.
GLORY/STP-01

teleased for
GLORY/STP-01

date
16/06/2012

SCHEMATIC FLOW DIAGRAM
SCAILE
N.T.S.

ANAND HAVELIA

SLUDGE HOLDING

TANK1

## **DEEPAK MEHTA & ASSOCIATES**

PLOT NO. 16 ABHISHEK PLAZA LSC MAYUR VIHAR PH II, DELHI PH: 6527-2180

## services consultant

2.

3.

4.

5.

6.

7.

9.

10.

11.

12.

1.

2.

AIR BLOWER - 3 NOS. IN ONE SET (2W+1S)

SCREW PUMPS - 2 NOS. IN ONE SET (1W+1S)

BALANCE RAW SEWAGE TRANSFER PUMPS

DEWATERING PUMPS - 2 NOS. IN ONE SET

FILTER PRESS - 1 SET (30 X 30 INCH - 29 PLATES)

- 3 NOS. IN ONE SET (2W+1S)

- 3 NOS. IN ONE SET (2W+1S)

MULTIGRADE FILTER - 1 SET

**ACTIVATED CARBON FILTER - 1 SET** 

**OZONATOR - 1 SET** 

FILTER FEED PUMPS - 2 NOS. IN ONE SET (1W+1S)

SLUDGE DISPOSAL PUMPS - 3 NOS. IN ONE SET (2W+1S)

HYDROPNEUMATIC WATER SUPPLY PUMPING SYSTEM

IRRIGATION WATER TRANSFER PUMPS - 2 NOS. IN ONE SET (1W+1S

## Consummate Engineering Services (P) Ltd.

FLOW RATE - 22 CUM/HR AT 20 HRS. OPERATION FOR 440 KLD CAP

FLOW RATE - 22 CUM/HR AT 20 HRS. OPERATION FOR 440 KLD CAP

Noida Office: A - 48, Sector - 52, Noida - 201 307 Tel: (0120) 4233034 / 4233035 Fax: (0120) 2585577 Lko. Office: 3 / 179, Vivek Khand, Gomti Nagar, Tel: (0522) 4005455 / 2395487 Fax: (0522) 2395487 e mail: mail@cespl.in website: www.cespl.in

FILTER DETAILS:

200 CUM/HR

10 METER

40 METER

35 METER

35 METER

15 METER

12 METER

9 CUM/HR

3 CUM/HR

22 CUM/HR

20 CUM/HR

15 CUM/HR

4 LPS

200 GRMS/HR

1400Ø

NOT IN THE PRESENT SCOPE

OF STP CONTRACTOR