

Specification

1. P.C.C. floor in 1:6:12 (1 cement, 6 coarse) C.sand F.M. 2.20-3.50) sand and 12, 40 mm. gauge brick ballast.
2. Class-150 brick in foundation & plinth in 1:6 cement & coarse sand mortar. (coarse sand F.M. 1.50 to 2.20)
3. 230 mm. Class -150 brick work in S/S in 1:6 cement & C. sand mortar . (coarse sand F.M. 1.50 to 2.20)
4. 115 mm. thick Class-150 brick work in S/S in 1:4 cement & C. sand mortar . (coarse sand F.M. 1.50 to 2.20)
5. 12 mm. thick plaster in 1:6 cement & C. sand mortar . (coarse sand F.M. 1.50 to 1.75)
6. R.C.C lintel, beam & slab in 1:1½:3 coarse sand and 3, 20 mm. graded stone grit.
7. Floor-300x300mm. Kajaria Tiles. *or any approved make .*
8. Bath & W.C., 300x300mm. ~~Antiskid~~ tiles in floor & 300x200mm. Glazed tiles in wall.
9. Door Chaukhat- 35x35x5mm. angle iron.
10. Window- Z-Section.
11. Door shutter- Flush door shutter.
12. Fittings- Oxidized fittings.
13. W.C. & Bath- S.W.R. PVC pipe, C.P.V.C. Pipe.
14. Internal Electric wiring- Copper wiring.

Boul.
OB

Prull
AB 15/13

Prull
DE 13

Prull
BB