

**PMAY-MAK INFRACITY PVT LTD AT AMBABAI-JHANSI (UP)**

<b>List of Specification</b>	
	AS PER PRADHAN MANTRI AWAS YOJANA
1	CIVIL WORKS
	BASE CONCRETE
	FOUNDATION BASE CONCRETE 1:4:8
	R C C IN FOUNDATION
	M -20 GRADE 1:1.5:3
	RC C COLUMN /LINTAL/BEAM/SLAB
	M -20 GRADE 1:1.5:3
	SUPERSTRUCTURE
	230MM THICK BRICK WALL/115MM THICK BRICK WALL
	PLASTER
	INNER AND OUTER 12MM THICK CEMENT PLASTER IN 1:6 CEMENT AND COARSE SAND
	KITCHEN TOP
	PLAIN C C TOP
	FLOOR AND WALL TILES
	1-300X300 MM FLOOR TILES OF APPROVED MAKE OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND
	2-200X300 MM OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND
	FINISHING
	1- OUTER FINISHING WITH TWO COAT OF APEX WHETHER COAT WITH BIRLA PUTTY
	2- INNER FINISH WITH 2 COAT COLOUR WASH DISTEMPER
	DOOR SHUTTER
	30MM THICK FLUSH DOOR SHUTTER ISI MARK
	WINDOW SHUTTER
	M S Z - SECTION WINDOW SHUTTER WITH 3 TO 4.7 MM THICK GLASS PANES ISI MARK
	WATER STORAGE TANK
	500 LITRE TRIPPLE LAYER PER POLYETHYLENE WATER STORAGE TANK
	ROOF TREATMENT
	BRICK COBA WITH KHURRA
2	WATER SUPPLY & SANITARY
	15/20/25 MM DIA B-CLASS CPVC PIPE WITH ALL REQUIRED FITTINGS ISI MARK
	ORRISA PATTERN W C PAN SIZE SIZE 580 MM ISI PARK
	15MMDIA BRASS BIB COCK 400 GM
3	ELECTRIFICATION
	COPPER CONCEALED WIRING WITH PVC CONDUIT PIPE IN SLAB AND ROOF
	POINTS
	LIGHT POINTS,FAN POINTS WITH RGULATOR,5 AMP PLUG POINTS & POWER PLUGS
	EARTHING
	AS PER REQUIREMENT OF SITE