


Specification of project

Provisions for EWS Houses

<u>S.N.</u>	<u>ITEM</u>	<u>Provision for EWS (G+3) Houses</u>
1	No. of storey	G+3
2	Multipurpose Room	2.70 X 3.00 = 8.10 Sqm
3	Room No. 2	2.70 X 3.00 = 8.10 Sqm
4	Kitchen (cooking platform)	1.57 X 1.73 = 2.72 Sqm
5	Bath	1.20 X 1.00 = 1.20 Sqm
6	W.C	1.00 X 1.00 = 1.00 sqm
7	Passage	1.12 X 1.39 = 1.56 Sqm
8	Balcony	1.59 X 1.12 = 1.78 sqm
9	Carpet area of one Unit (2+3+4+5+6+7+half of 8)	23.57 sqm
10	Super Area of one unit	37.91 sqm
11	Door frame	Angle iron single leaf
12	Window frame	Z-Section single leaf with grill


 A.F. / अमृतसंग नवाय विवाहित,
 अमृतसंग विकास प्राविकरण
 अमृतसंग


 B.E. / सावध
 अमृतसंग विकास प्राविकरण
 अलीगढ़

अमृतसंग विकास प्राविकरण
 अलीगढ़

Specification of four storey (G+3) proposed houses under

Pradhan Mantri Awas Yojna

• Civil Works

1	Base concrete	Foundation base concrete in 1:4:8 (1 cement : 4 coarse sand : 8 stone aggregate 40mm size)
2	R.C.C Foundation	M-20 graded 1:1.5:3 (1 cement : 1.5 coarse sand : 3 stone aggregate 20mm size)
3	R.C.C Column/Lintel/Beam/Slab	M-20 graded 1:1.5:3 (1 cement : 1.5 coarse sand : 3 stone aggregate 20mm size)
4	Super Structure	230 mm thick brick work in 1:6 cement and fine sand 1.25 FM and 115 mm thick brick work in 1:4 (1 cement : 4 coarse sand)
5	Plaster	Inner and outer 12 mm thick cement plaster in 1:6 (1 cement : 6 coarse sand)
6	Kitchen top	Plain C.C Top 1:2:4
7	Floor/Wall tiles	C.C Floor and W.C bath & kitchen walls with tile 6MM TH. with 1:4 cement coarse sand mortar
8	Finishing	Outer finishing with 2 coat of snowsome coat and internal finish with 2 coat colour wash distemper
9	Door shutter	30mm thick flush door shutter ISI mark
10	Window shutter	M.S Z-Section window shutter with 4 mm thick glass panes ISI mark.
11	Water storage tank	500 ltr. Triple layer per house polyethylene water storage tank.
12	Roof treatment	Brick coba with khurra.

• Water supply & sanitary

15/20/25 mm dia B class CPVC pipe with all required fittings ISI Mark.

Orrisa pattern W.C Pan size 580mm ISI mark.

15mm dia C.P brass bib cock 400gm.

• Electrification

Points:- Light point, Fan point with regulator, 5amp plug point &

15amp power plugs.

Earthing:- As per requirement of site.

मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
वर्तीयमंत्री

मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
वर्तीयमंत्री

मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
वर्तीयमंत्री

मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
मुख्यमंत्री प्रधानमंत्री विकास प्राधिकरण
वर्तीयमंत्री