SPECIFICATIONS

of Echilention	
STRUCTURE	
Earthquake Resistant	Combination of RCC Frame and Load bearing brick structure.
Structure	
External Wall Finish	Cement paint/Texture Finish
Internal Wall Finish	Oil Bound Distemper on walls and Ceiling
Flooring	Vitrified tiles in Drawing, Dinning and Bedrooms, Ceramic
	tiles in Store/Study
Doors	Hard wood Frame with Flush door shutter in paint/polish/skin moulded/flush doors.
External Doors and	Power coated/Anodized Aluminium/GI/wooden frame with
Windows	Aluminium/Wooden Shutters Glazing.
Hardware	Good quality/handles and fittings.
KITCHEN	
Walls	Combination of Ceramic tiles upto 2' above the counter and
	oil bound distemper in the balance area.
Flooring	Vitrified tiles/Ceramic Tiles/Stone
Counter	Granite/Marble/Baroda Green
Fittings and Fixtures	Good quality C.P. Fittings, SS Kitchen sink single bowl and
	drain board.
TOILETS	
Walls	Combination of Designer ceramic tiles upto 7", oil bound
	distemper.
Flooring	Ceramic tiles/stone.
Counter	Granite/Marble/Baroda Green with ceramic wash basin.
Fittings and Fixtures	Superior Quality C.P. Fittings, English type WC in
	white/pastel shade, Wash Basin, Mirror and Towel rod. One
	toilet with Type WC.
Electrical	Modular switches and sockets; copper wiring (fittings like
	fan, light, exhaust, geysers and appliance etc. not provided).
BALCONIES AND TERM	RACES
Flooring	Ceramic tiles/Stone
Ceiling	Exterior Piant
Staircase and Drive	Kota Stone/Tiles/Pavers Blocks/Combination of
Way	stone/Concrete
Roof Terrace	Brickbat Coba/equivalent treatment.