

	AS PER PRADHAN MANTRI AWAS YOJANA	AS PER ESTIMATE
CIVIL WORKS		
BASE CONCRETE	FOUNDATION BASE CONCRETE 1:4:8	FOUNDATION BASE CONCRETE 1:4:8
R C C IN FOUNDATION	M -20 GRADE 1:1.5:3	M -20 GRADE 1:1.5:3
/LINTAL/BEAM/SLAB	M -20 GRADE 1:1.5:3	M -20 GRADE 1:1.5:3
SUPERSTRUCTURE	230MM THICK BRICK WALL/115MM THICK BRICK WALL	AAC BLOCK 230 MMTHICK/100 MMTHICKinstead of brick work
PLASTER	INNER AND OUTER 12MM THICK CEMENT PLASTER IN 1:6 CEMENT AND COARSE SAND	12MM THICK OUTER AND 12MMTHICK INNER PLASTER IN 1:4 CEMENT AND COARSE SAND
KITCHEN TOP	PLAIN C C TOP	300X300 MM FLOOR TILES OF APPROVED MAKE OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND
FLOOR AND WALL TILES	1 -300X300 MM FLOOR TILES OF APPROVED MAKE OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND	1 -300X300 MM FLOOR TILES OF APPROVED MAKE OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND
	2 -200X300 MM OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND	2 -200X300 MM OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND
FINISHING	1 -OUTER FINISHING WITH TWO COAT OF APEX WHETHER COAT WITH BIRLA PUTTY	1 -OUTER FINISHING WITH TWO COAT OF APEX WHETHER COAT WITH BIRLA PUTTY
	2 - INNER FINISH WITH 2 COAT COLOUR WASH DISTEMPER	2 - INNER FINISH WITH OIL BOUND
DOOR SHUTTER	30MM THICK FLUSH DOOR SHUTTER ISI MARK	30MM THICK FLUSH DOOR SHUTTER COMMERCIAL QUALITY ISI MARK
WINDOW SHUTTER	M S Z - SECTION WINDOW SHUTTER WITH 3 TO 4.7 MM THICK GLASS PANES ISI MARK	M S Z - SECTION WINDOW SHUTTER WITH 3 TO 4.7 MM THICK GLASS PANES ISI MARK
WATER STORAGE TANK	500 LITRE TRIPPLE LAYER PER POLYETHYLENE WATER STORAGE TANK	500 LITRE TRIPPLE LAYER PER POLYETHYLENE WATER STORAGE TANK
ROOF TREATMENT	BRICK COBA WITH KHURRA	BRICK COBA WITH KHURRA
WATER SUPPLY & SANITARY		
	15/20/25 MM DIA B-CLASS CPVC PIPE WITH ALL REQUIRED FITTINGS ISI MARK	15/20/25 MM DIA B-CLASS CPVC PIPE WITH ALL REQUIRED FITTINGS ISI MARK
	ORRISA PATTERN W C PAN SIZE SIZE 580 MM ISI PARK	ORRISA PATTERN W C PAN SIZE SIZE 580 MM ISI PARK
	15MMDIA BRASS BIB COCK 400 GM	15MMDIA BRASS BIB COCK 400 GM
ELECTRIFICATION		
	COPPER CONCEALED WIRING WITH PVC CONDUIT PIPE IN SLAB AND ROOF	COPPER CONCEALED WIRING WITH PVC CONDUIT PIPE IN SLAB AND ROOF & WALL
POINTS	LIGHT POINTS,FAN POINTS WITH RGULATOR,5 AMP PLUG POINTS & POWER PLUGS	LIGHT POINTS,FAN POINTS ,5 AMP PLUG POINTS & POWER PLUGS
EARTHING	AS PER REQUIREMENT OF SITE	ONE EARTHING FOR ONE BLOCK (48 HOUSES)