

PMAY-RADHASWAMI INFRADEVELOPERS PVT LTD, AT KARAI, JHANSI (UP)

| List of Specification | | |
|------------------------------|-------------------------------|--|
| | | AS PER PRADHAN MANTRI AWAS YOJANA |
| 1 | CIVIL WORKS | |
| | BASE CONCRETE | FOUNDATION BASE CONCRETE 1:4:8 |
| | R C C IN FOUNDATION | M -20 GRADE 1:1.5:3 |
| | RC C COLUMN /LINTAL/BEAM/SLAB | M -20 GRADE 1:1.5:3 |
| | SUPERSTRUCTURE | 230MM THICK BRICK WALL/115MM THICK BRICK WALL |
| | PLASTER | INNER AND OUTER 12MM THICK CEMENT PLASTER IN 1:6 CEMENT AND COARSE SAND |
| | KITCHEN TOP | PLAIN C C TOP |
| | FLOOR AND WALL TILES | 1-300X300 MM FLOOR TILES OF APPROVED MAKE OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND |
| | | 2-200X300 MM OVER 20 MM THICK CEMENT MORTOR OF 1:4 CEMENT AND COARSE SAND |
| | FINISHING | 1-OUTER FINISHING WITH TWO COAT OF APEX WHETHER COAT WITH BIRLA PUTTY |
| | | 2- INNER FINISH WITH 2 COAT COLOUR WASH DISTEMPER |
| | DOOR SHUTTER | 30MM THICK FLUSH DOOR SHUTTER ISI MARK |
| | WINDOW SHUTTER | M S Z - SECTION WINDOW SHUTTER WITH 3 TO 4.7 MM THICK GLASS PANES ISI MARK |
| | WATER STORAGE TANK | 500 LITRE TRIPPLE LAYER PER POLYETHYLENE WATER STORAGE TANK |
| | ROOF TREATMENT | BRICK COBA WITH KHURRA |
| 2 | WATER SUPPLY & SANITARY | |
| | | 15/20/25 MM DIA B-CLASS CPVC PIPE WITH ALL REQUIRED FITTINGS ISI MARK |
| | | ORRISA PATTERN W C PAN SIZE SIZE 580 MM ISI PARK |
| | | 15MMDIA BRASS BIB COCK 400 GM |
| 3 | ELECTRIFICATION | |
| | | COPPER CONCEALED WIRING WITH PVC CONDUIT PIPE IN SLAB AND ROOF |
| | POINTS | LIGHT POINTS,FAN POINTS WITH RGULATOR,5 AMP PLUG POINTS & POWER PLUGS |
| | EARTHING | AS PER REQUIREMENT OF SITE |