

## General Specifications

**Name of work:-** Construction of 69 Nos. 69/142 Type Houses in Sector-3 at Scheme No. 11, Jagriti Vihar (Ext.), Meerut.


- |   |                               |   |
|---|-------------------------------|---|
| 1 | Foundation Concrete           | 40mm gauge stone ballast Coarse sand & cement mortar in proportion of 8:4:1   |
| 2 | Brick work in foundation      | M-150 Class Brick work in 1:6 cement and coarse sand (FM 1.50-2.00) mortar.   |
| 3 | Brick work in Super Structure | M-150 Class Brick work in 1:6 cement and coarse sand mortar for one brick thick wall & in 1:4 cement and coarse sand mortar for half brick thick walls.                         |
| 4 | R.C.C. work                   | All R.C.C. work shall be in 1:1½:3 cement coarse sand & stone grit.   |
| 5 | Chaukhats                     | All door and window chaukhats shall be of 35x35x5mm Angle iron.   |
| 6 | Plaster                       | Wall plaster shall be in 1:6 cement and coarse sand mortar (FM 1.50-2.00) <del>ceiling plaster shall be cement brick in 1:3 cement and fine sand mortar.</del>                  |
| 7 | Door shutters                 | Only outer doors 30mm thick flush door shutters.  |
| 8 | Finishing                     | All interior walls & ceiling are finished with Birla wall putty & Exterior walls are finished with weather coats and grills & shutter are painted with synthetic enamel paints. |
| 9 | Electrification               | Only fan boxes and PVC conduit shall laid in slab and walls.  |

  
J.E.

  
A.E.

  
J.E.(T)

  
E.E.

  
अधीक्षक अभियन्ता  
दिलीप नृत  
आवास एवं विकास परिषद  
मेरठ।