


SPECIFICATION

NAME OF WORK- CONSTRUCTION OF TYPE 36/75 AT BHUMI VIKAS EVAM GRAH SATHAN YOJANA -3 JHANSI.

- 1- **Foundation** – Foundation design as per soil test Report.
- 2- **Foundation Concrete** – Foundation Concrete provided in cement, Coarse sand and 40mm gauge stone ballast in proportion of 1:4:8.
- 3- **Structure** –Composite Structure (Partially load bearing and partially RCC framed Structure.
- 4- **Height of Plinth** – 0.60 cm above from road in front of proposed building.
- 5- **Pre-An termite Treatment**- Pre Constructional ant termite Treatment shall be provided according to soil Conditions of soil present at site and as recommended by architect concern.
- 6- **Earth quake resistant** – as recommended by architect concern.
- 7- **Super Structure masonry** – Class 150 Brick work in 1:6 Cement S Coarse sand mortar in brick thick or above wall & ½ brick thick wall in 1:4 cement & Coarse sand mortar.
- 8- **R.C.C. Work** – Lintel, loft beam & Slab width & thickness as per design R.C.C. in 1.1.5.3 Cement Coarse sand & 20mm gauge stone grit.
- 9- **Chaukhat & Shutters** – M.S. angle 40x40x6mm provided in door chaukhat & 38cm thick flush door shutter provided and 2 section frame & shutter shall be provided in windows and ventilator.
- 10- **Door Fittings** – Stainless Steel door fitting shall be provided.
- 11- **Roof Treatment** – Average 12cm thick brick coba shall be provided.
- 12- **Plaster work** – 12mm thick Plaster on face & 15mm thick plaster on rough face to of wall with 1:6 Cement and Coarse sand mortar.
- 13- **Floor, Dado & Skirting** - Kota stone / Verified tiles/ glazed tiles will be provided on floor over 8cm thick base C C. 1:5:10 in cement, Coarse sand & 40mm stone ballast joint free tiles/ glazed tiles will be provided in dado and skirting upto required height as mentioned in working drawing of building concerned.
- 14- **Finishing work**- In side of building oil bound distemper outer side building water proof exterior apex paint and doors, windows frames & Shutters shall be painted with enamel paint, Three coat white wash in Ceiling.
- 15- **Internal water Supply and Sanitary** – 580mm Orissa pattern/ European type white glazed W.C. seat with automatic flushing cistern Glazed china wash basin, Glazed China Urinals, Glazed China laboratory sink, 75mm & 100mm UPVC-SWR pipe and their fittings, CPVC pipe and their fittings, beveled edge mirror, PVC water storage tank etc. will be provided as mentioned in working drawing of building concerned.
- 16- **Internal Electrification** – Copper wire shall be provided in wiring. All wiring with PVC conduit pipe shall be concealed. All of the fittings, fixtures and panels etc. will be provided as mentioned in working drawing of building concerned.


AE.