

Specification

Foundation Concrete 1:5:10 (1 cement: 5 fine sand 1.25fm: 10 Brick ballast)

Foundation Concrete 1:4:8 (1 cement: 4 coarse sand 2.20fm: 8 Stone ballast)

RCC in raft foundation 1:1.5:3 (1 cement: 1.5 coarse sand 2.20fm: 3 Stone grite)

RCC in Column 1:1.5:3 (1 cement: 1.5 coarse sand 2.20fm: 3 Stone grite)

RCC in lintal 1:1.5:3 (1 cement: 1.5 coarse sand 2.20fm: 3 Stone grite)

RCC in Slab M-25 grade RMC

Brick work in foundation 1:4 (1 cement : 4 coarse sand 2.20fm)

Brick work in Super structure 1:4 (1 cement : 4 coarse sand 2.20fm)

12mm thick plaster in 1:4 cement and fine sand

15mm thick plaster on rough face in 1:4 cement and fine sand

2.5cm thick plane CC floor in 1:2:4 (1 cement: 2 coarse sand 2.20fm: 4 Stone grite)

Door leaf 35mm thick flush door shutter commercial quality.

Mud phaska 100mm thick

20mm thick kota stone (florrying and stairs)

6mm china white glased tiles

White wash in three coat

Finishing wall with water proof cement paint