

I.NO.	ITEM DESCRIPTION	SPECIFICATION (6)
1	B/W in supper Structure.	Class 150 in 1:6 cement & coarse sand 23cm thick, 1:6 cement coarse sand 11.5cm thick.
2	Plinth Beam	RMC-M20
3	Footling	R.M.C-(M-20) Grade
4	Chaukhats for Doors.	Angle iron frame.
5	Grill for windows	Z-Section window with M.S. Grill in 8 mm square bars.
6	Doors shutters in Rooms & Toilets	30mm thick phenol bonded flush door shutter.
7	Window & vent. Shutters.	Z-Section with Glazing.
8	Door fitting	Oxidised iron fitting.
9	Roof Treatment	Brick coba treatment.
10	Wall Plaster outside	12mm thick plaster in 1:3 cement and coarse sand mortar of FM (1.50 to 1.75)
11	Wall Plaster inside	12mm thick plaster in 1:6 cement and coarse sand mortar of FM (1.50 to 1.75)
12	Ceiling Plaster inside	6 mm thick plaster in 1:3 cement and coarse sand mortar c FM (1.25)
13	Flooring	B/R, Living Room ,Kitchen-Ceramic Glazed Floor Tile with base concrete 1:4:8
		Toilet & Bath - Antiskid Floor Tile with base concrete 1:4:8
14	Internal Finish	3 coat of Lime colour wash.
15	External finish	Finishing Wall with 2 coat of Sandtex matt/APEX weather coat paint with 1 priming coat
16	Painting	2 coat of Ready mixed paint or varnish over one coat of ready mix priming paint.
17	Apron	25 mm thick C.C in 1:2:4 over 80 mm thick base concrete 1:4:8 (cement : coarse sand : 40mm stone grit base concrete)
17	Rain water pipe	110 mm PVC pipe
	<u>Water supply & sanitary work</u>	
18	WC seat	White Orissa pattern with flushing cistern.
19	Water point	Brass bibcock.
20	P.P.R Pipe	20 / 25mm dia
21	Water storage tank	300 ltr. PVC water storage tank as per approved make.

J.E.

A.E.

J.E.(T)

E.E.